



**GALLO
ACOUSTICS**



**HABITAT
MICRO & A'DIVA**

OWNER'S GUIDE



INTRODUCTION

Thank you for choosing Gallo Acoustics HABITAT loudspeakers.

HABITAT speakers are IP66 rated and have been designed for use outdoors or in humid or wet environments such as bath, shower or pool rooms.

Please take the time to read and understand this guide thoroughly before installing your loudspeakers. This will ensure that you achieve optimal performance without the risk of causing damage to your speakers or amplifier.

OPTIONAL ACCESSORIES

Available from your dealer, or directly from www.galloacoustics.com

WALL MOUNT

Weatherproof wall mounts for the Micro and A'Diva HABITAT models are available in black, white and stainless steel finishes.

RUN-IN PERIOD

Your Gallo HABITAT loudspeaker utilises proprietary technologies that only reach their optimum performance levels after a period of between 60 - 80 hours of use.

During this run-in process the loudspeaker driver will loosen-up, the patented S2 fill material will settle, and your loudspeakers will develop the acoustic characteristics that are our signature.

GROUND SPIKE

An optional ground spike is available to allow HABITAT speakers to be installed at ground level, either as a feature in an exposed area, or concealed in landscaping. A pivot at the top of the spike allowing the speaker to be angled towards the intended listening position.

INSTALLATION & SET UP

Select the appropriate mounting option for your specific installation, and mount the speaker in the desired location.

HABITAT speakers are hardwired with 2 metres of weatherproof cable. The cable can be routed through a wall for connection indoors, or alternatively to a suitable waterproof junction box (or similar) for an external connection to the system speaker cables.

Please ensure that your amplifier is turned off before connecting the speakers, and ensure that correct polarity is observed.

In either stereo or multi-channel systems, HABITAT loudspeakers are designed to be used in conjunction with a subwoofer so the full frequency image can be heard - this is especially important with the Micro HABITAT variant.

When using HABITAT speakers, you must employ a suitable crossover or filter to ensure that only frequencies of 80Hz and above are sent to the loudspeakers.

Attempting playback of lower frequencies can cause permanent damage to the loudspeaker and invalidate the warranty.

Consult your subwoofer and amplifier owner's guides for more detailed set up instructions.

SPECIFICATIONS

	MICRO HABITAT	A'DIVA HABITAT
Frequency Response	100Hz to 18kHz	80Hz to 20kHz
Sensitivity	86 +/- 2 dB (1m)	85 +/- 2 dB/ (1M)
Nominal Impedance	8 Ohms	8 Ohms
Power Handling	Full range - 50 Watts With crossover - 100 Watts	Full range - 50 Watts With crossover - 100 Watts
Crossover	None	None
Driver	3" full range waterproof	3" full range waterproof
Dimensions	4" sphere	5" sphere
Weight	745g excl. cable	970g excl. cable
Cone Material	Mical polypropylene compound	Mical polypropylene compound
Enclosure Material	Marine grade stainless steel (316)	Marine grade stainless steel (316)
IP Rating	IP66	IP66
Operating Temperature	-20 to +50 °C	-20 to +50 °C
Warranty	5 years	5 years

WARNING

Care must be taken when installing or mounting this product on walls, ceilings or surfaces.

Appropriate fasteners must be used (where required) to ensure the safe installation of both the speakers and mounts.

Care should be taken to ensure that any external connections are made within a waterproof junction box.

If you are in any way unsure of the correct installation, assembly or use then please consult qualified sources before taking unnecessary risks.

The manufacturer, distributor or their agents cannot be held responsible for any injury as a result of improper use or installation of this product.

TECHNICAL SUPPORT

Should you encounter problems using this product, please contact your dealer or local distributor.

You can call Gallo Acoustics directly for technical support on the following numbers:

UK
01555 666883

Outside UK
+44 1555 666883

United States, Canada and South America
+1 (646) 873 6900

Alternatively, email -
support@galloacoustics.com

WARRANTY

Anthony Gallo Acoustics Ltd warrants to the end user that this product will be free from defects in materials and workmanship in the course of normal use for a period of five years from the date of purchase.

This guarantee covers breakdowns due to manufacturing faults and does not apply in cases such as accidental damage, general wear and tear, user negligence, improper installation, modification or repair not by Anthony Gallo Acoustics Ltd.

www.galloacoustics.com





ANTHONY GALLO ACOUSTICS LTD
THE INOX BUILDING
CALDWELLSIDE
LANARK
SCOTLAND
UNITED KINGDOM
ML11 7SR

WWW.GALLOACOUSTICS.COM
